

FTK 8.2 SP3 SITE SERVER GUIDE

OCTOBER 2026

Table of Contents

About Exterro	3
1 Site Server Changes	3
2 Impacts for 8.2 SP3	3
2.1 Site Server Configuration Impacts	3
3 Parameters	4
4 Backward Compatibility.....	13
Contact Exterro	15

About Exterro

Exterro was founded with the simple vision that applying the concepts of process optimization and data science to how companies manage digital information and respond to litigation would drive more successful outcomes at a lower cost. We remain committed to this vision today. We deliver a fully integrated Data Risk Management platform that enables our clients to address their privacy, regulatory, compliance, digital forensics, and litigation risks more effectively and at lower costs. We provide software solutions that help some of the world's largest organizations, law enforcement and government agencies work smarter, more efficiently, and support the Rule of Law.

1 Site Server Changes

The 8.2 SP3 version of Exterro FTK Site Servers allows an agent to configure and establish connections to multiple regions of Public Site Servers simultaneously without having to uninstall and reconfigure the same agent for each region's Public Site Servers. Moreover, you can trigger jobs from different instances for a single agent.

From 8.2 SP3 version, the **Site Server instance** field will be enabled in for the **Root** type Site Server and the value provided in this field will be reflected for all the corresponding child site servers. You can view that information in the child site server UI, but it cannot be edited.

2 Impacts for 8.2 SP3

2.1 Site Server Configuration Impacts

- The 'Agent Collection' option has been split into 'Windows Collection' and 'Linux Collection'. Enabling any of these options on a Site Server will trigger collection for that specific operating system. This setting is not applicable to Public Site Servers.

3 Parameters

Parameters	Description	Default Values	Values
SSLIST	Consists of the entire list of Private or Public Site Servers (DNS or Network Load Balancers or IP) without any port numbers	-	"PUB1SS,PUB2SS,DNS1,DNS2,NLB1,NLB2"
HTTPSPORT	The HTTPS Check-in port number. Note: Only a single value can be provided for this parameter. For the users with multiple regions, the same check-in port number should be used across all available regions of the Site Server.	443	Any valid port number
TCPPORT	The Public TCP Port number. Note: Only a single value can be provided for this parameter. For the users with multiple regions, the same Public TCP Port number should be used across all available regions of the Site Server.	54545	Any valid port number
CHECKIN	0 - The check-in will stop upon successful check-in to one of the Site Server in SSLIST 1 - The check-in will not stop successful check-in and will continue to check in for all available Site Servers in SSLIST	0	0 1
CER=	Full path to the public certificate. Path must be enclosed in quotes if it contains spaces. Acceptable certificate formats are P7B, P7C, DER, CER, and CRT.	N/A	Public certificate path

Parameters	Description	Default Values	Values
INSTALLDIR=	Specifies a desired path to install the agent. Path must be enclosed in quotes if it contains spaces. If not specified, the default value is assumed.	C:\Program Files\AccessData\Agent	The path where the installation should be performed
PORT=	The port that the agent will be listening on. If not specified, the default value is assumed.	3999	A valid port number
STORESIZE=	Specifies the agent temporary data storage size. If not specified, the default value is assumed.	268435456	The value larger than or equal to the default value should be provided
SYSTEMSIZE=	Specifies the agent configuration files storage size. If not specified, the default value is assumed.	16777216	The value larger than or equal to the default value should be provided
TRANSIENT=	Installs an Agent that will expire and uninstall itself after the next reboot or restart of the service	0	0 1
LIFETIME=	Specifies the amount of time that an agent will exist before self-destructing. A negative value is used to denote minutes (eg: -30 denotes 30 minutes), and a positive value is used to denote days (eg: 30 denotes 30 days).	0	Positive (days) or negative (minutes) value should be provided.
SERVICELESS =	Installs as a one-shot, ephemeral Agent that runs only as a process, and uninstalls itself on the next reboot. A 1 enables this feature. If not specified, the default value is assumed.	0	0 1
FIREWALL_RULE=	The name of the firewall rule is created when an agent has been installed	FTK Enterprise Agent	The rule's name based on your preference.
NOT_CREATE_FIREWALLRULE	A 1 indicates that the agent, when installed will not create a firewall rule at all. A 0	0	0 1

Parameters	Description	Default Values	Values
	indicates it will install the agent with a firewall rule.		
retry_failed_attempt	If a Public Site Server is not passed as a parameter, then the value will always remain at 0 - this means the agent will behave as it does as standard. If a Public Site Server and retry_failed_attempt parameter is passed, an agent will restart automatically once it fails to connect to a Public Site Server after the passed value.	5	The required number of attempts
HTTPS_CER_ENABLE	1 - indicates to check the certificate is domain registered or CA Certificate if not the connection will be established in TCP and 0 does not check the certificate is registered or CA certificate and establish the HTTPS connection with PFX Certificate	1	0 1
PING_SIZE	The Ping Size represents the number of bytes of data transferred for checking Latency.	5242880	The required Ping size
ENABLE_LOGGING	1 indicates that the agent log is enabled. 0 Indicates agent log is disabled. The agent log can be found within: C:\Program Files\AccessData\Agent\Agent.log	1	0 1
INSTALL_REMOTE	0 indicates that the agent will not install the necessary dependencies for remote mobile collections	1	0 1

Parameters	Description	Default Values	Values
	1 indicates that the agent will install the necessary dependencies for remote mobile collections Additionally agent will report back within the data sources tab (FTK Central) as a RMD agent.		
RMD_PATH	Where mobile collection jobs will create and store collected data before transferring to the site server.	C:\Program Files\AccessData\Agent\config\netfs.exe	Any folder Path of the computer (Example: D:\AD1_Path - D:\ Drive Name AD1_Path -- Folder Path)
DO_LATENCY	1 represents before the job start ping will be sent to all the available Site Server instances and job run on the Site Server with lower latency 0 represent the ping call will not be sent and the job will run on the same Site server instance where the HTTPS Check-in happened	1	0 1
EXECNAME	The agentcore executable file will be renamed to the provided name. Note: Ensure the service/exe name contains no spaces, or special characters (other than . or -) to avoid check-in failures.	agentcore	<name>.exe

Parameters	Description	Default Values	Values
SERVICENAME	The name of the service will be changed to the provided value. Note: Ensure the service name contains no spaces, as this can cause check-in failures.	AgentService- <version_number>	<Name_of_Service>
REMEDiate	To install the 'remediate-<version>' module in the following location: C:\Program Files\AccessData\Agent\modules	1	1 - To install the module 0 - To not install the module

Note: The 8.2 SP3 agent can be installed with the older arguments and after installation the arguments will be converted to latest arguments.

Example:


8.2 SP3:

```
msiexec /I "<Location_of_MSI>" CER="<Location_of_CRT>" SSLIST="FQDN1,FQDN2" HTTPSPORT=443
TCPSPORT=54545
```

Workflow when CHECKIN value is set to 0:

The Site Servers mentioned on the IPLIST parameter will be checked sequentially until one of the IP is checked in successfully. During the first check-in, the process will be made for all IPs in the list. After the first IP is checked-in, the remaining IPs in the list will not be checked-in.

This should be used for a Single Root Site Server consisting of multiple Public and Private Site Servers.




Workflow when CHECKIN value is set to 1:

All the Site Servers mentioned in the IPLIST parameter will be checked for each periodic check-in.

Once a check-in is successfully done, then the check-in will be continued through the Site Server for all the remaining Ips.

This should be used for Multiple Root Site Servers and Multiple Public/Private Site Servers in different regions.



Parallel Check-in:

- The parallel check-in happens to the Site Server to update the agent's last contact details when the job is in progress.
- The parallel check-in starts after 2 minutes of the job start and the consecutive check-in happens based on the check-in interval set.
- The parallel check-in stops once the job gets completed and the regular check-in will start to happen.
- The parallel check-in will update only the agent's last contact details and if any job is available it will not be picked up by the agent.
- The parallel check-in will happen only via HTTPS check-in.

Note: TCP check-in will not happen even if all the HTTPS check-ins fail.

- The parallel check-in is controlled by the CHECKIN parameter and follows the same behavior as CHECKIN = 0 and 1.

Check-in behavior:

- The Site Server type will be updated on the HTTPS check-in.
- The consecutive check-ins from the agent to Site Server will follow a flow where the agent will try to connect to the Site Server type 0,1 and 2:
 - SS Type 0 - Unable to connect to the Site Server and unable to determine the Site Server type.
 - SS type 1 - Indicates the Site Server is private.
 - SS type 2 - Indicates the Site Server is public.

Site Server Configuration Change:

- The following fields' names have been renamed:

Previous name	New name
Max Incoming Thread	Max Agent Thread
Outgoing Thread	Max Job Thread

- The 'Max SS Incoming Thread' field is newly added to set the maximum number of threads for handling incoming Site Server-to-Site Server connections on port **54548**. The default value for this field is 50.

Agent.ini file change:

- The **agent.ini** file contains only the following arguments and corresponding values.

```
MaxThreads=33
Port=3990
Cert=C:\CustomPath\config\SelfSignedCert.crt
TrustedAuth=C:\CustomPath\config\95728BA1-5406-4732-84A2-C1B5A76BCB61-adata.p7b
RetryFailedAttempt=5
HttpsCerEnable=1
Sslist=gaejpublicss.exterrocloud.info
Tcpport=54545
Httpsport=443
Checkin=1
EnableLog=1
RMDpath=
Install_RMD=1
dolatency=1
ExpiredTime=0
```

However, a file named 'agentinstallcommands.txt' containing all parameters (default and custom) will be stored in the Config folder.

- The values can be handled from the agent.ini file (i.e. when edited and restarted, new values will be considered for the arguments).

Site Server instance value update:

- The user can install the agent by providing only one value on the SSLIST argument.
- The rest of the values will be updated on the agent if the agent check-in is successful.

4 Backward Compatibility

FTK Site Server is enhanced with Backward compatibility, the process of ensuring the older versions (before 8.2 SP3) of Agents (along with the latest) will work without any issues with the latest version of Site Server. The Backward Compatibility process is performed differently for each versions of Agent based on the description provided below:

Agent MSI COMMAND	Backward Compatibility	
8.2	agent.ini	Comments
msiexec /i<"AGENT MSI LOCATION"> CER=<"CERTIFICATE LOCATION"> FOLDER_STORAGE=1 PUBSS=<"URL:54545"> HTTPS_HOST_PORT=<"PUBSSURL1:443,PUBSSURL2:443,PUBSSURL3:443">	Pubss=PubliURL1:54545 Port value won't be updated on the agent.ini	Initially, for all the available PUBSS URL (HTTPS URL), the check-in will happen through the corresponding port. After that, the check-in will happen based on the value configured in the managed API.
8.2 SP2	agent.ini	Comments
msiexec /i<"AGENT MSI LOCATION"> CER=<"CERTIFICATE LOCATION"> FOLDER_STORAGE=1 SSLIST=<"PUBSSURL"> HTTPSPORT=443 TCPPOINT=54545	Sslist=PublicURL1,PrivateURL1 Tcpoint=54545 Httpsport Value won't be updated in agent.ini	8.2 SP2 supports only one Port With Single/Multiple PUBSS URL (HTTPS URL)
8.2 SP2 HF6	agent.ini	Comments
msiexec /i<"AGENT MSI LOCATION"> CER=<"CERTIFICATE LOCATION"> SSLIST=<"PUBSSURL"> HTTPSPORT=443 TCPPOINT=54545	Sslist=PublicURL1,PrivateURL1 Tcpoint=54545 Httpsport Value won't be updated in agent.ini	8.2 SP2 HF6 supports only one Port With Single/Multiple PUBSS URL (HTTPS URL)
8.2 SP2 HF7	agent.ini	Comments
msiexec /i<"AGENT MSI LOCATION"> CER=<"CERTIFICATE LOCATION"> SSLIST=<"PUBSSURL"> HTTPSPORT=443 TCPPOINT=54545	Sslist=PublicURL1,PrivateURL1 Tcpoint=54545 Httpsport Value won't be updated in agent.ini	8.2 SP2 HF7 supports only one Port With Single/Multiple PUBSS URL (HTTPS URL)

Notes:

- The check-in will happen on the HTTPS and the job will run on the 54545 port.
- Agent Backward compatibility for the private and public setups of site server will work only for the 8.2 and later versions of Windows Agent.
- If multiple ports were used in PUBSS in the previous versions of Site Server (before 8.2 SP2), it needs to be updated to use only a single port while configuring the Site Server. You should ensure it is consistent when using PUBSS/https in 8.2 SP2 otherwise, things won't work correctly.

Supported versions:

Agent (8.2 and 8.2 SP1 | 8.2.0.174), Agent (8.2 SP2 HF5 | 8.2.2.36), Agent (8.2 SP2 HF6 | 8.2.3.40), Agent (8.2 SP2 HF7 | 8.2.3.89)

Contact Exterro

If you have any questions, please refer to this document, or any other related materials provided to you by Exterro. For usage questions, please check with your organization's internal application administrator. Alternatively, you may contact your Exterro Training Manager or other Exterro account contact directly.

For technical difficulties, support is available through support@exterro.com.

Contact:**Exterro, Inc.**

2175 NW Raleigh St., Suite 110

Portland, OR 97210.

Telephone: 503-501-5100

Toll Free: 1-877-EXTERRO (1-877-398-3776)

Fax: 1-866-408-7310

General E-mail: info@exterro.com

Website: www.exterro.com

Information in this document is subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Exterro, Inc. The trademarks, service marks, logos or other intellectual property rights of Exterro, Inc and others used in this documentation ("Trademarks") are the property of Exterro, Inc and their respective owners. The furnishing of this document does not give you license to these patents, trademarks, copyrights or other intellectual property except as expressly provided in any written agreement from Exterro, Inc.

The United States export control laws and regulations, including the Export Administration Regulations of the U.S. Department of Commerce, and other applicable laws and regulations apply to this documentation which prohibits the export or re-export of content, products, services, and technology to certain countries and persons. You agree to comply with all export laws, regulations and restrictions of the United States and any foreign agency or authority and assume sole responsibility for any such unauthorized exportation.

You may not use this documentation if you are a competitor of Exterro, Inc, except with Exterro Inc's prior written consent. In addition, you may not use the documentation for purposes of evaluating its functionality, or for any other competitive purposes.

If you have any questions, please contact Customer Support by email at support@exterro.com.